

LED High Bay Light Series: HBH1





Features & Benefits:

- 1.Glare reduction with sand-blasting safety glass cover
- 2. Universal voltage input, 100~240VAC which covers most of worldwide common used voltage
- 3. Suitable for ceiling up to 7 meters in height
- 4. Energy saving up to 70% from HID or mercury lamp
- 5.100% recyclable, UV free
- 6. Fast response and flickering free

Application:

Direct illumination source for industrial use: Suitable for warehouse, gyms, assembly areas, etc.


Light Up Your Life




Specification

Item #	HBH1-100
Wattage	100W
CCT	4000 ± 250°K ; 6000± 250°K
Light fixture (lm)	≥6100
RA	≥70
Input voltage	AC 100V ~ 240V , 50/60Hz
Power factor	≥0.8
Power efficiency	≥85%
Weight (kg)	3.15
Beam angle	80°
Working condition	-25°C ~ 40°C ,<70%RH
Storage condition	-40°C ~ 60°C ,<70%RH
Diameter (mm)	430
Height (mm)	450
illuminance(1M)	4540 lux
Body material	Aluminum

Diameter



Polar graph



Kaohsiung City 806, Taiwan(R.O.C)
TEL : 886-7-8159877 • FAX : 886-7-8156711

E-Mail : led@lasertek.com.tw

Light Up Your Life